## In the Claims1

Please amend claims 21, 26-27, 51-54 and 61 to read as follows:

as or

- (Twice amended) A scrubbing process for the abatement of a gas component in a gas stream containing same, said scrubbing process comprising introducing the gas stream and a scrubbing liquid to a first gas/liquid contacting chamber and effecting gas/liquid contacting therein, wherein said process additionally at least one of the steps of:
- (a) introducing a chemical reagent for contact with the gas component to remove same from the gas stream in said gas/liquid contacting;
- (b) introducing to the gas stream prior to entry thereof into the contacting chamber, a gas to enhance removal of silane from the gas stream when present therein;
- (c) flowing the effluent gas from the first contacting chamber to a second gas/liquid contacting chamber and introducing to said second contacting chamber a second scrubbing liquid for gas/liquid contacting therein, wherein the first gas/liquid contacting in the first chamber comprises cocurrent flow of the gas stream and scrubbing liquid and wherein the second gas/liquid contacting in the second contacting chamber comprises countercurrent flow of the gas stream and the second scrubbing liquid through the second contacting chamber, wherein said second contacting chamber has a smaller volume than that of said first contacting chamber, and wherein the second contacting chamber has a lower water flow rate than the first contacting chamber;
- (d) introducing an antifoam agent to scrubbing liquid for said gas/liquid contacting, to suppress foam production in the contacting chamber;

Consistent with the requirements of 37 C.F.R. §1.121, a marked up version of the amended claims is contained in Appendix A hereof; a clean copy of all pending claims is contained in Appendix B hereof. Consistent with the holding of Festo Corp. v. Shoketsu Kinzoku Kogyo Kabushiki Co., Ltd., et al., 535 U.S. \_\_\_\_ (2002), decided May 28, 2002, any amendments herein that hereafter are deemed to be narrowing amendments by a court of competent jurisdiction in a final unappealed or unappealable decision, are not intended to relinquish any scope of equivalents unforeseeable at the time of this amendment or that relate to aspects of the invention having only a peripheral relation to the basis for the amendment.

ans DIT

suppressing deposition of calcium carbonate from scrubbing liquid containing calcium, including a step selected from the group consisting of:

- (1) imposing a magnetic field on scrubbing liquid prior to use thereof in the contacting chamber;
- (2) adjusting the pH of the scrubbing liquid to maintain pH thereof below 8.5;
  flowing the scrubbing liquid through a lime-soda ash bed prior to use of the scrubbing liquid in the contacting chamber; and
- (4) precipitating the calcium content of the scrubbing liquid prior to use of the scrubbing liquid in the contacting chamber; and
- (f) suppressing solids formation in a passage of the scrubbing system, said passage comprising a conduit to a pressure sensing device, including a step selected from the group consisting of flowing a purge gas through the passage to suppress solids formation therein, and heating the passage to suppress solids formation therein.

Greas 18

26. (Twice Amended) A scrubbing process for treatment of an effluent gas including acid gas components and water-scrubbable components other than acid gas component, said process comprising:

skrubbing the effluent gas with a neutral aqueous scrubbing liquid in a first scrubbing zone to remove the acid gas components of the effluent gas, with co-current flow contacting of the aqueous scrubbing liquid and effluent gas with one another to yield effluent gas reduced in acid gas components;

()

flowing the effluent gas reduced in acid gas components from the first scrubber unit to a second scrubber unit; and

scrubbing the effluent gas with a second aqueous scrubbing liquid in the second scrubbing zone to remove water-scrubbable components other than acid gas component from the effluent gas, with counter-current flow contacting of the second aqueous scrubbing liquid and effluent gas with one another to yield effluent gas reduced in acid gas components and water-scrubbable components other than acid gas components, wherein said second scrubbing zone has a volume smaller than that of said first scrubbing zone, and wherein the second scrubbing zone has a lower water flow rate than the first scrubbing zone chamber.

27. (Twice Amended) The process according to claim 26, wherein the first scrubbing zone is a vessel enclosing an interior volume containing a bed of packing medium.

ms 037

(Amended) The process according to claim 26 wherein the scrubbing liquid in the second scrubbing zone contains no caustic chemical injection agent.

- 52. (Amended) The process according to claim 21 wherein the scrubbing liquid in the first contacting chamber and second chamber is neutral water.
- 53. The process according to claim 21 wherein the first scrubbing liquid contains no caustic chemical injection agent.
- 54. (Amended)The process according to claim 21 wherein the second scrubbing liquid contains no caustic chemical injection agent.
- 61. (Amended) A scrubbing process for the abatement of a gas component in a gas stream containing same, said scrubbing process comprising:

introducing the gas stream and a scrubbing liquid to a first gas/liquid contacting chamber and effecting gas/liquid contacting therein; flowing the effluent gas from the first contacting chamber to a second gas/liquid contacting chamber and introducing to said second contacting chamber a second scrubbing liquid for gas/liquid contacting therein, wherein the first gas/liquid contacting in the first chamber comprises co-current flow of the gas stream and scrubbing liquid, and wherein the second gas/liquid contacting in the second contacting chamber comprises countercurrent flow of the gas stream and the second scrubbing liquid through the second contacting chamber, wherein said second contacting chamber has a smaller volume than that of said first contacting chamber, and wherein the second contacting chamber has a lower water flow rate than the first contacting chamber.

CAP CAP

Please cancel claims 59 and 60, the contents of which have been included in claims 21 and 26, respectively. Thus, amended claims 21 and 26 with the limitations of claims 59 and 60 have already been examined by the Office. Also, please cancel claims 63 and 64.